

DOOR SCHEDULE

MARK	WIDTH	HEIGHT	TYPE	FRAME	FIRERATING	HARDWARE	UNDERCUT	UVALUE	JAMBDETAIL
	3'-0"	6'-8"	3068 Solid Core Wood	HM	20-min	HW-01	0.75		
	6'-0"	6'-8"	6068 Double Aluminum Storefront	aluminum		HW-05			
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	16'-0"	6'-8"	8080 Overhead Sectional	none					
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	3'-0"	0'-0"	Single Door 36"						
	3'-0"	6'-8"	3068 Solid Core Wood	HM	20-min	HW-01	0.75		
	3'-0"	6'-8"	3068 Solid Core Wood	HM	20-min	HW-01	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3068 Hollow Core Wood	wood		HW-02	0.75		
	2'-8"	6'-8"	3070 Solid Core, 45-min FR	HM	45-min	HW-03	0.75		

GLAZING & HARDWARE LEGEND

	TG — TEMPERED GLAZING (IRC R308.4)
	EG — EGRESS WINDOW (IRC R310, 5.7 SF)
	HW-1 — ENTRY LOCKSET + DEADBOLT
	HW-2 — PRIVACY LATCH
	HW-3 — PASSAGE LATCH
	HW-4 — SELF-CLOSING, 20-MIN RATED

WINDOW SCHEDULE

MARK	WIDTH	HEIGHT	OPERATION	FRAME/MATERIAL	GLAZING	UVALUE	SHGC	STC
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	6'-0"	4'-0"	sliding	aluminum	double-tempered			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	4'-0"						
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	4'-0"	4'-0"	casement	clad-wood	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	3'-0"	5'-0"	single-hung	vinyl	double-low-e			
	2'-0"	3'-0"	fixed	vinyl	double-low-e			
	4'-0"	4'-0"	casement	clad-wood	double-low-e			

DOOR & WINDOW NOTES

1. EXTERIOR DOORS: INSULATED, WEATHER-STRIPPED, U'd 0.30. WINDOWS: U'd 0.30, SHGC'd 0.40 (IECC 5B).
2. VERIFY ROUGH OPENINGS WITH MANUFACTURER PRIOR TO FRAMING.
3. TEMPERED GLAZING WITHIN 24" OF DOORS, AT TUB/SHOWER ENCLOSURES AND < 18" A.F.F. PER IRC R308.4.
4. EGRESS WINDOWS: 5.7 SF NET CLEAR, 24" MIN HEIGHT, 20" MIN WIDTH, 44" MAX SILL (R310).